

Kawasaki

2016 MULE™ SIDE X SIDES



2016

MULE® SIDE X SIDE SPECS

MULE™ 4010 TRANS4x4®

MULE™ 4010 TRANS4x4® SE

ENGINE	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled
DISPLACEMENT	617cc	617cc
BORE X STROKE	76.0 x 68.0mm	76.0 x 68.0mm
COMPRESSION RATIO	10.3:1	10.3:1
MAXIMUM TORQUE	34.7 lb-ft @ 2500 rpm	34.7 lb-ft @ 2500 rpm
FUEL SYSTEM	DFI® w/ 34mm Mikuni throttle body	DFI® w/ 34mm Mikuni throttle body
IGNITION	Digital electronic	Digital electronic
TRANSMISSION	Continuously Variable Transmission (CVT) with high and low range, forward, neutral and reverse, 2WD/4WD	Continuously Variable Transmission (CVT) with high and low range, forward, and reverse, 2WD/4WD
FINAL DRIVE	Shaft, selectable 4-wheel drive with dual-mode rear differential	Shaft, selectable 4-wheel drive with dual-model differential
ALTERNATOR OUTPUT (MAX)	23 amp	23 amp
FRONT SUSPENSION / WHEEL TRAVEL	Independent, MacPherson strut/3.9 in	Independent, MacPherson strut/3.9 in
REAR SUSPENSION / WHEEL TRAVEL	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in
FRONT TIRES	23x11-10 tubeless	23x11-10 tubeless
REAR TIRES	23x11-10 tubeless	23x11-10 tubeless
STEERING	Electric power assisted rack-and-pinion	Electric power assisted rack-and-pinion
FRONT BRAKES	4-wheel hydraulic drums, sealed	4-wheel hydraulic drums, sealed
REAR BRAKES	4-wheel hydraulic drums, sealed	4-wheel hydraulic drums, sealed
GROUND CLEARANCE	7.1 in	7.1 in
FUEL CAPACITY	6.3 gal	6.3 gal
TURNING RADIUS	12.8 ft	12.8 ft
ROLL OVER PROTECTIVE STRUCTURE (ROPS)	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement
CARGO BED DIMENSIONS (LXWXH)	50.4/30.3 x 47.6 x 11.2 in	50.4/30.3 x 47.6 x 11.2 in
CARGO BED CAPACITY	400 lb/800 lb (4/2-pass mode)	400 lb/800 lb (4/2-pass mode)
LOAD CAPACITY	1330 lb	1330 lb
SEATING CAPACITY	4 (2 front/2 rear)	4 (2 front/2 rear)
TOWING CAPACITY	1200 lb	1200 lb
LIGHTING	(2) 35-watt sealed-beam headlights, (2) 5/21-watt tail/brake lights	(2) 35-watt sealed-beam headlights, (2) LED auxiliary lights, (2) 5/21-watt tail/brake lights
FRAME TYPE	Steel tube ladder type	Steel tube ladder type
OVERALL LENGTH	128.5 in	128.5 in
OVERALL WIDTH	58.5 in	58.5 in
OVERALL HEIGHT	75.8 in	78.1 in
CURB WEIGHT	1,586.9 lb**	1,619.9 lb**
WHEELBASE	85.2 in	85.2 in
INSTRUMENTS	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet
COLOR CHOICES	Timberline Green, Dark Royal Red	Super Black
WARRANTY	Kawasaki Strong 3 Year Limited Warranty	Kawasaki Strong 3 Year Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24 or 36 months	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Specifications subject to change.

Realtree APG-XTRA Camouflage Design © 2012 of Jordan Outdoor Enterprises, Ltd., all rights reserved.

MULE™ 4010 TRANS4x4® CAMO

MULE™ 4010 4x4

ENGINE	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled
DISPLACEMENT	617cc	617cc
BORE X STROKE	76.0 x 68.0mm	76.0 x 68.0mm
COMPRESSION RATIO	10.3:1	10.3:1
MAXIMUM TORQUE	34.7 lb-ft @ 2500 rpm	34.7 lb-ft @ 2500 rpm
FUEL SYSTEM	DFI® w/ 34mm Mikuni throttle body	DFI® w/ 34mm Mikuni throttle body
IGNITION	Digital electronic	Digital electronic
TRANSMISSION	Continuously Variable Transmission (CVT) with high and low range, forward, and reverse, 2WD/4WD	Continuously Variable Transmission (CVT) with high and low range, forward, and reverse, 2WD/4WD
FINAL DRIVE	Shaft, selectable 4-wheel drive with dual-model differential	Shaft, selectable 4-wheel drive with dual-model differential
ALTERNATOR OUTPUT (MAX)	23 amp	23 amp
FRONT SUSPENSION / WHEEL TRAVEL	Independent, MacPherson strut/3.9 in	Independent, MacPherson strut/3.9 in
REAR SUSPENSION / WHEEL TRAVEL	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in
FRONT TIRES	23x11-10 tubeless	23x11-10 tubeless
REAR TIRES	23x11-10 tubeless	23x11-10 tubeless
STEERING	Electric power assisted rack-and-pinion	Electric power assisted rack-and-pinion
FRONT BRAKES	4-wheel hydraulic drums, sealed	4-wheel hydraulic drums, sealed
REAR BRAKES	4-wheel hydraulic drums, sealed	4-wheel hydraulic drums, sealed
GROUND CLEARANCE	7.1 in	6.9 in
FUEL CAPACITY	6.3 gal	6.3 gal
TURNING RADIUS	12.8 ft	11.2 ft
ROLL OVER PROTECTIVE STRUCTURE (ROPS)	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement
CARGO BED DIMENSIONS (LXWXH)	50.4/30.3 x 47.6 x 11.2 in	46.3 x 51.6 x 11.4 in
CARGO BED CAPACITY	400 lb/800 lb (4/2-pass mode)	800 lb
LOAD CAPACITY	1330 lb	1330 lb
SEATING CAPACITY	4 (2 front/2 rear)	2
TOWING CAPACITY	1200 lb	1200 lb
LIGHTING	(2) 35-watt sealed-beam headlights, (2) 5/21-watt tail/brake lights	(2) 35-watt sealed-beam headlights, (2) 5/21-watt tail/brake lights
FRAME TYPE	Steel tube ladder type	Steel tube ladder type
OVERALL LENGTH	128.5 in	116.7 in
OVERALL WIDTH	58.5 in	62.0 in
OVERALL HEIGHT	75.8 in	75.8 in
CURB WEIGHT	1,586.9 lb**	1,432.6 lb**
WHEELBASE	85.2 in	73.6 in
INSTRUMENTS	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet
COLOR	Realtree Xtra® Green Camo	
COLOR CHOICES		Timberline Green, Dark Royal Red
WARRANTY	Kawasaki Strong 3 Year Limited Warranty	Kawasaki Strong 3 Year Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24 or 36 months	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

2016

MULE® SIDE X SIDE SPECS

MULE™ 4010 4x4 SE

MULE™ 4000

ENGINE	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled	4-stroke, 2-cylinder, OHV Valve 90° V Liquid-cooled
DISPLACEMENT	617cc	617cc
BORE X STROKE	76.0 x 68.0mm	76.0 x 68.0mm
COMPRESSION RATIO	10.3:1	10.3:1
MAXIMUM TORQUE	34.7 lb-ft @ 2500 rpm	34.7 lb-ft @ 2500 rpm
FUEL SYSTEM	DFI® w/ 34mm Mikuni throttle body	DFI® w/ 34mm Mikuni throttle body
IGNITION	Digital electronic	Digital electronic
TRANSMISSION	Continuously Variable Transmission (CVT) with high and low range, forward, and reverse, 2WD/4WD	Continuously Variable Transmission (CVT) with forward and reverse
FINAL DRIVE	Shaft, selectable 4-wheel drive with dual-model differential	Shaft, dual-mode rear differential dual-model differential
ALTERNATOR OUTPUT (MAX)	23 amp	23 amp
FRONT SUSPENSION / WHEEL TRAVEL	Independent, MacPherson strut/3.9 in	Independent, MacPherson strut/3.9 in
REAR SUSPENSION / WHEEL TRAVEL	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in
FRONT TIRES	23x11-10 tubeless	23x11-10 tubeless
REAR TIRES	23x11-10 tubeless	23x11-10 tubeless
STEERING	Electric power assisted rack-and-pinion	Rack-and-pinion
FRONT BRAKES	4-wheel hydraulic drums, sealed	4-wheel hydraulic drums, sealed
REAR BRAKES	4-wheel hydraulic drums, sealed	4-wheel hydraulic drums, sealed
GROUND CLEARANCE	6.9 in	7.5 in
FUEL CAPACITY	6.3 gal	6.3 gal
TURNING RADIUS	11.2 ft	11.0 ft
ROLL OVER PROTECTIVE STRUCTURE (ROPS)	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement
CARGO BED DIMENSIONS (LXWXH)	46.3 x 51.6 x 11.4 in	46.3 x 51.6 x 11.4 in
CARGO BED CAPACITY	800 lb	800 lb
LOAD CAPACITY	1330 lb	1330 lb
SEATING CAPACITY	2	2
TOWING CAPACITY	1200 lb	1200 lb
LIGHTING	[2] 35-watt sealed-beam headlights, [2] LED auxiliary lights, [2] 5/21-watt tail/brake lights	[2] 35-watt sealed-beam headlights, [2] 5/21-watt tail/brake lights
FRAME TYPE	Steel tube ladder type	Steel tube ladder type
OVERALL LENGTH	116.7 in	116.7 in
OVERALL WIDTH	62.0 in	62.0 in
OVERALL HEIGHT	78.1 in	75.8 in
CURB WEIGHT	1445.8 lb**	1,338.4 lb**
WHEELBASE	73.6 in	73.6 in
INSTRUMENTS	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet	Parking brake and coolant temp warning lights, horn, 12V DC outlet
COLOR CHOICES	Super Black	Timberline Green, Dark Royal Red
WARRANTY	Kawasaki Strong 3 Year Limited Warranty	Kawasaki Strong 3 Year Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24 or 36 months	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change.

MULE™ 610 4x4 XC**MULE™ 610 4x4 XC SE**

ENGINE	4-stroke, 1-cylinder, OHV, Air-cooled	4-stroke, 1-cylinder, OHV, Air-cooled
DISPLACEMENT	401cc	401cc
BORE X STROKE	82.0 x 76.0mm	82.0 x 76.0mm
COMPRESSION RATIO	8.6:1	8.6:1
MAXIMUM TORQUE	21.7 lb-ft @ 2400 rpm	21.7 lb-ft @ 2400 rpm
FUEL SYSTEM	Nikki 6C1026	Nikki 6C1026
IGNITION	Magneto and transistor	Magneto and transistor
TRANSMISSION	Continuously Variable Transmission (CVT) with high and low range, reverse	Continuously Variable Transmission (CVT) with high and low range, reverse
FINAL DRIVE	Shaft-driven selectable 4-wheel drive, dual-mode rear differential	Shaft-driven selectable 4-wheel drive, dual-mode rear differential
ALTERNATOR OUTPUT (MAX)	17 amp	17 amp
FRONT SUSPENSION / WHEEL TRAVEL	MacPherson strut/3.1 in	MacPherson strut/3.1 in
REAR SUSPENSION / WHEEL TRAVEL	Unit swingarm, adjustable shocks/3.1 in	Unit swingarm, adjustable shocks/3.1 in
FRONT TIRES	AT26 x 9R -12 Maxxis tubeless	AT26 x 9R -12 Maxxis tubeless
REAR TIRES	AT26 x 9R -12 Maxxis tubeless	AT26 x 9R -12 Maxxis tubeless
STEERING	Rack-and-pinion	Rack-and-pinion
FRONT BRAKES	4-wheel hydraulic drums, triple sealed	4-wheel hydraulic drums, triple sealed
REAR BRAKES	4-wheel hydraulic drums, triple sealed	4-wheel hydraulic drums, triple sealed
GROUND CLEARANCE	8.1 in	8.1 in
FUEL CAPACITY	4.1 gal	4.1 gal
TURNING RADIUS	11.8 ft (differential unlocked)	11.8 ft (differential unlocked)
ROLL OVER PROTECTIVE STRUCTURE (ROPS)	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement
CARGO BED DIMENSIONS (LXWXH)	41.1 x 35.4 x 9.6 in	41.1 x 35.4 x 9.6 in
CARGO BED CAPACITY	399 lb	399 lb
LOAD CAPACITY	926 lb	904 lb
SEATING CAPACITY	2	2
TOWING CAPACITY	1100 lb	1100 lb
LIGHTING	(2) 35w headlights, and tail/brake light	(2) 35w headlights, and tail/brake light
FRAME TYPE	Steel tube ladder type	Steel tube ladder type
OVERALL LENGTH	108.5 in	108.5 in
OVERALL WIDTH	52.0 in	53.5 in
OVERALL HEIGHT	73.8 in	74.8 in
CURB WEIGHT	1,056.2 lb**	1,078.0 lb**
WHEELBASE	70.1 in	70.1 in
INSTRUMENTS	Oil temperature meter, hour meter	Oil temperature meter, hour meter
COLOR	Super Black	Super Black
WARRANTY	Kawasaki Strong 3 Year Limited Warranty	Kawasaki Strong 3 Year Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24 or 36 months	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

2016

MULE® SIDE X SIDE SPECS

MULE™ 610 4x4 XC CAMO

MULE™ 610 4x4

ENGINE	4-stroke, 1-cylinder, OHV, Air-cooled	4-stroke, 1-cylinder, OHV, Air-cooled
DISPLACEMENT	401cc	401cc
BORE X STROKE	82.0 x 76.0mm	82.0 x 76.0mm
COMPRESSION RATIO	8.6:1	8.6:1
MAXIMUM TORQUE	21.7 lb-ft @ 2400 rpm	21.7 lb-ft @ 2400 rpm
FUEL SYSTEM	Nikki 6C1026	Nikki 6C1026
IGNITION	Magneto and transistor	Magneto and transistor
TRANSMISSION	Continuously Variable Transmission (CVT) with high and low range, reverse	Continuously Variable Transmission (CVT) with high and low range, reverse
FINAL DRIVE	Shaft-driven selectable 4-wheel drive, dual-mode rear differential	Shaft-driven selectable 4-wheel drive, dual-mode rear differential
ALTERNATOR OUTPUT (MAX)	17 amp	17 amp
FRONT SUSPENSION / WHEEL TRAVEL	MacPherson strut/3.1 in	MacPherson strut/3.1 in
REAR SUSPENSION / WHEEL TRAVEL	Unit swingarm, adjustable shocks/3.1 in	Unit swingarm/3.1 in
FRONT TIRES	AT26 x 9R -12 Maxxis tubeless	24x9-10 tubeless
REAR TIRES	AT26 x 9R -12 Maxxis tubeless	24x11-10 tubeless
STEERING	Rack-and-pinion	Rack-and-pinion
FRONT BRAKES	4-wheel hydraulic drums, triple sealed	4-wheel hydraulic drums, triple sealed
REAR BRAKES	4-wheel hydraulic drums, triple sealed	4-wheel hydraulic drums, triple sealed
GROUND CLEARANCE	8.1 in	6.7 in
FUEL CAPACITY	4.1 gal	4.1 gal
TURNING RADIUS	11.8 ft (differential unlocked)	10.8 ft
ROLL OVER PROTECTIVE STRUCTURE (ROPS)	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement
CARGO BED DIMENSIONS (LXWXH)	41.1 x 35.4 x 9.6 in	41.1 x 35.4 x 9.6 in
CARGO BED CAPACITY	399 lb	399 lb
LOAD CAPACITY	926 lb	926 lb
SEATING CAPACITY	2	2
TOWING CAPACITY	1100 lb	1100 lb
LIGHTING	(2) 35w headlights, and tail/brake light	(2) 35w headlights, and tail/brake light
FRAME TYPE	Steel tube ladder type	Steel tube ladder type
OVERALL LENGTH	108.5 in	108.8 in
OVERALL WIDTH	52.0 in	52.6 in
OVERALL HEIGHT	73.8 in	70.9 in
CURB WEIGHT	1,069.0 lb**	1,020.9 lb**
WHEELBASE	70.1 in	70.0 in
INSTRUMENTS	Oil temperature meter, hour meter	Oil temperature meter, hour meter
COLOR CHOICES	Realtree Xtra® Green Camo	Timberline Green, Dark Royal Red
WARRANTY	Kawasaki Strong 3 Year Limited Warranty	Kawasaki Strong 3 Year Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24 or 36 months	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change.

Realtree APG-XTRA Camouflage Design © 2012 of Jordan Outdoor Enterprises, Ltd., all rights reserved.

MULE™ 610 4x4 SE**MULE™ 600**

ENGINE	4-stroke, 1-cylinder, OHV, Air-cooled	4-stroke, 1-cylinder, OHV, Air-cooled
DISPLACEMENT	401cc	401cc
BORE X STROKE	82.0 x 76.0mm	82.0 x 76.0mm
COMPRESSION RATIO	8.6:1	8.3:1
MAXIMUM TORQUE	21.7 lb-ft @ 2400 rpm	20.3 lb-ft @ 2200 rpm
FUEL SYSTEM	Nikki 6C1026	Nikki 6C1026
IGNITION	Magneto and transistor	Magneto and transistor
TRANSMISSION	Continuously Variable Transmission (CVT) with high and low range, reverse	Continuously Variable Transmission (CVT) with forward and reverse
FINAL DRIVE	Shaft-driven selectable 4-wheel drive, dual-mode rear differential	Shaft, dual-mode rear differential
ALTERNATOR OUTPUT (MAX)	17 amp	17 amp
FRONT SUSPENSION / WHEEL TRAVEL	MacPherson strut/3.1 in	MacPherson strut/3.1 in
REAR SUSPENSION / WHEEL TRAVEL	Unit swingarm, adjustable shocks/3.1 in	Unit swingarm, adjustable shocks/3.1 in
FRONT TIRES	24x9-10	22x9-10 tubeless
REAR TIRES	24x11-10	22x11-10 tubeless
STEERING	Rack-and-pinion	Rack-and-pinion
FRONT BRAKES	4-wheel hydraulic drums, triple sealed	4-wheel hydraulic drums, triple sealed
REAR BRAKES	4-wheel hydraulic drums, triple sealed	4-wheel hydraulic drums, triple sealed
GROUND CLEARANCE	6.7 in	6.1 in
FUEL CAPACITY	4.1 gal	4.1 gal
TURNING RADIUS	10.8 ft	10.8 ft
ROLL OVER PROTECTIVE STRUCTURE (ROPS)	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement	Structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, and 7.5 and meets the FMVSS 216 Roof Crush resistance requirement
CARGO BED DIMENSIONS (LXWXH)	41.1 x 35.4 x 9.6 in	41.1 x 35.4 x 9.6 in
CARGO BED CAPACITY	399 lb	399 lb
LOAD CAPACITY	917 lb	926 lb
SEATING CAPACITY	2	2
TOWING CAPACITY	1100 lb	1100 lb
LIGHTING	(2) 35w headlights, and tail/brake light	(2) 35w headlights, and tail/brake light
FRAME TYPE	Steel tube ladder type	Steel tube ladder type
OVERALL LENGTH	108.8 in	108.8 in
OVERALL WIDTH	52.6 in	52.6 in
OVERALL HEIGHT	70.9 in	70.1 in
CURB WEIGHT	1,078.0 lb**	956.5 lb**
WHEELBASE	70.0 in	70.0 in
INSTRUMENTS	Oil temperature meter, hour meter	Hour meter
COLOR CHOICES	Sunbeam Red	Timberline Green, Dark Royal Red
WARRANTY	Kawasaki Strong 3 Year Limited Warranty	Kawasaki Strong 3 Year Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24 or 36 months	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

WARRANTY

Every Kawasaki MULE™ side x side is backed with a Kawasaki STRONG 3-Year Limited Warranty. Ask your dealer for details about the factory warranty and available extended coverage.

UP TO THREE YEARS ADDITIONAL COVERAGE

Let Kawasaki protect your new vehicle for years to come with Kawasaki Protection Plus™. This plan repairs or replaces most components free of charge if found defective in material or workmanship. Everything about the plan is easy: There's no deductible. It's honored at every authorized Kawasaki dealer nationwide. It's transferable to another owner with no fee. Just ask your dealer how you can buy additional coverage of 12, 24, or 36 months. Depending on the model and plan purchased. FL Lic #65500, Kawasaki Motors Corp., U.S.A., PO Box 25252, Santa Ana, CA 92799, (949) 770-0400.

KAWASAKI CARES: Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x sides are off-highway vehicles only, and are not designed, equipped, or manufactured for use on public streets; roads or highways. Obey the laws and regulations that control the use of your vehicle. Read Owner's Manual and all on product warnings.



Kawasaki subscribes to the guidelines of Tread Lightly!® a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.

